



# United States Geological Survey Certificate of Analysis

## Manganese Nodule, NOD-A-1

NOD-A-1 is a reference material which can be used to establish analytical accuracy in the analysis of manganese nodules or other geologic samples with elevated manganese concentrations. Material used in the preparation of the standard was collected from the Atlantic ocean along the Blake Plateau (31° 02' N, 78° 22' W) at a depth of 788 meters (Flanagan and Gottfried, 1980).

Recommended concentrations for elements and oxides are reported when results from USGS interlaboratory studies (Flanagan and Gottfried, 1980) using independent methods of analysis are in statistical agreement. Supplemental information derived from international data compilations (Abbey, 1983, Govindaraju, 1994) is also provided.

Information concentrations are given when results are based on analyses obtained using a single technique or when data from different procedures are not in statistical agreement.

### Recommended values

Oxide	Wt %	±	Oxide	Wt %	±
SiO <sub>2</sub>	3.81	0.047	MnO	23.9	0.065
Al <sub>2</sub> O <sub>3</sub>	3.87	0.060	Na <sub>2</sub> O	1.0	0.008
Fe <sub>2</sub> O <sub>3 tot</sub>	15.6	0.060	K <sub>2</sub> O	0.6	0.010
CaO	15.4	0.054	TiO <sub>2</sub>	0.53	0.007
MgO	4.76	0.016	P <sub>2</sub> O <sub>5</sub>	1.40	0.016

  

Element	µg/g	±	Element	µg/g	±
Ba	1670	31	Pb	846	8
Co	3110	11	Sr	1750	14
Cu	1100	10	V	770	6
Mo	448	9	Zn	590	5
Ni	6360	24			

### Information values

Element	µg/g	Element	µg/g
Ce	730	La	120
Dy	23	Lu	2.2
Er	12	Nd	94
Eu	5	Sm	21
Gd	26	Yb	14

## Bibliography

Abbey, S., 1983, Studies in "Standard Samples" of Silicate Rocks and Minerals 1969-1982, Canadian Geological Survey paper 83-15, p-114.

Flanagan, F.J. and Gottfried, D., 1980, USGS Rock Standards, III: Manganese-Nodule Reference Samples USGS-Nod-A-1 and USGS-Nod-P-1, U.S. Geological Survey Professional Paper, 1155, p-39

Govindaraju, K., 1994, 1994 Compilation of Working Values and Descriptions for 383 Geostandards, Geostandards Newsletter, 18:1-158

## Glossary

Fe <sub>2</sub> O <sub>3</sub> T	Total iron expressed as Fe <sub>2</sub> O <sub>3</sub>
C <sub>tot</sub>	Total concentration of carbon
S <sub>tot</sub>	Total concentration of sulfur
Wt %	Percent of total element concentration
µg/g	Total element concentration expressed as micrograms of element per gram of solid sample
±-	One standard deviation

## Notes

### Drying instructions

Prior to analysis samples of NOD-A-1 should be dried at 110 °C for 24 hours. Samples should be stored in a desiccator if not used immediately. Reports indicate that NOD-A-1 can absorb up to 10% by weight of moisture when exposed overnight to air .

## Ordering Information

USGS reference materials (RMs) may be obtained directly from Dr. Stephen A. Wilson at the address or numbers listed below. The price for each bottle of RM is \$ 80.00 (U.S.) **except** DGPM-1 which is \$175.00 (U.S.). This cost includes all shipping and handling charges using normal mail delivery. Urgent requests for RMs should be initiated by FAX or e-mail. If required, overnight delivery is available with these charges added to the final bill.

Dr. Stephen A. Wilson  
U.S. Geological Survey  
Box 25046, MS 964  
Denver, CO 80225

Tel: 303-236-2454  
FAX: 303-236-3200 or 303-236-1425  
e-mail: [swilson@usgs.gov](mailto:swilson@usgs.gov)

## Payment Options

**Domestic customers:** Payment options include purchase order, check, money order, or credit card (Visa, Mastercard).

**International customers:** Payment on foreign orders may be made by any of the following:

- Banker's draft against an international bank,
- International money order,

c. Credit card (Visa, Mastercard)

Payments for domestic or international orders using a credit card receive a 10% discount on the per bottle price.

---